



ProtoRC_r0 wired for OVRCLK65

- T1 to pin2 of 6-pin serial port
- T2 to pin3 of 6-pin serial port
- T3 to pin2 (RDY) of W65C816
- T4 to pin4 (IRQ) of W65C816
- T5 to pin6 (NMI) of W65C816
- T6 to pin7 (VPA) of W65C816
- T7 to pin9 (A0) of W65C816
- T8 to pin10 (A1) of W65C816
- T9 to pin11 (A2) of W65C816
- T10 to pin12 (A3) of W65C816
- T11 to pin13 (A4) of W65C816
- T12 to pin14 (A5) of W65C816
- T13 to pin15 (A6) of W65C816
- T14 to pin16 (A7) of W65C816
- T15 to pin17 (A8) of W65C816
- T16 to pin18 (A9) of W65C816
- T17 to pin19 (A10) of W65C816
- T18 to pin20 (A11) of W65C816
- T19 to pin22 (A12) of W65C816
- T20 to pin23 (A13) of W65C816
- T21 to pin24 (A14) of W65C816
- T22 to pin25 (A15) of W65C816
- T23 to pin26 (D7) of W65C816
- T24 to pin27 (D6) of W65C816
- T25 to pin28 (D5) of W65C816
- T26 to pin29 (D4) of W65C816
- T27 to pin30 (D3) of W65C816
- T28 to pin31 (D2) of W65C816
- T29 to pin32 (D1) of W65C816
- T30 to pin33 (D0) of W65C816
- T31 to pin34 (RW) of W65C816
- T32 to pin39 (VDA) of W65C816
- T33 to pin35 (E) of W65C816